



1550nm Direct Modulation Optical Transmitter · MX-T1500A Series

Technical Specification



PRODUCT DESCRIPTION

The Maxcom MX-T1500A is a 1550nm direct modulation optical transmitter with high index and AGC function. Maxcom incorporates a high linearity and a low chirp DFB laser, built-in pre-distortion compensation and AGC, APC, ATC closed loop control, which improve the performance index. It may be used in a FTTx application for transmitting Digital QAM CATV and DOCSIS RF signals over fiber. Optimized for networks under 30km using an EDFA. This transmitter may also be ordered with Optional WDM narrow-band laser (standard ITU wavelengths available).

- MX-T1500AC optical transmitter: Standard CATV wavelength
- MX-T1500AU optical transmitter: ITU standard DWDM wavelength



PRODUCT FEATURES

- Low chirp, high linearity DFB laser, chirp compensation.
- Dual module RF driver, highly efficient laser pre-distortion adjustment.
- Full-automatic OMI control, AGC & MGC.
- Modulation status display.
- Standard optical output is +10 dBm
- Auto temperature control to ensure long laser life.
- Commonly used in RFoG or RF Overlay networks 30km or less, while maintaining good MER



www.maxcomcorp.com 209-339-2333

Technical Index



Performance			Index	Supplement
Optic feature	Wavelength	(nm)	1548~1563	MX-T1500AC: CATV wavelength
			1530~1563	MX-T1500AU: ITU wavelength
	Linewidth	(MHz)	≤1	FWHM($\Delta\lambda$)
	Side mode suppression ratio	(dB)	≥45	SMSR
	Extinction ratio	(dB)	≥20	Xp
	Equivalent noise intensity	(dB/Hz)	≤-160	RIN (20~1000MHz)
	Output power	(dBm)	10	Optional 3, 6
	Return loss	(dB)	≥55	
RF feature	optical fiber connector		SC/APC	
	Work bandwidth	(MHz)	47~1000	
	Input level	(dBmV)	20±2	MGC
	Flatness	(dB)	≤±0.75	47~1000 MHz
	Return loss	(dB)	>16	
	Input impedance	(Ω)	75	RF/INPUT
Link feature	RF test	(dB)	0±1	
	Transmit channel		PAL-D/60CH	NTSC/80CH
	CNR	(dB)	≥50	-1dBm receive
	CTB	(dB)	≤-63	
	CSO	(dB)	≤-57	
General feature	SBS restrain	(dBm)	≥17	
	Network Mgmt. interface		RJ45, RS232	Support I.E., & SNMP
	Power supply	(V)	90~265AC power	-48VDC optional
	Power Consumption	(W)	≤50	Single power supply
	Operating temp.	(°C)	-5~65	Auto temp. control
	Storage temp.	(°C)	-40~85	
	Relative humidity	(%)	5~95	
Size		(")	19×10×1.75	(W)x(D)x(H)